



Email: sales@marinabayside.com.au
Website: https://www.marinabayside.com.au/
1-13 Mangrove Lane Taren Point NSW 2229



F225

POA







Specifications

Boat Details

Price POA Boat Brand Yamaha Model F225 Length 0.00

Year 2024 Category Boat Engines and Outboards

Hull Style Hull Type


Power Type Power Stock Number F225XCB

Condition New State New South Wales

Suburb TAREN POINT Engine Make

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.





Email: sales@marinabayside.com.au Website: https://www.marinabayside.com.au/ 1-13 Mangrove Lane Taren Point NSW 2229

Description

Next generation features, next generation styling, original reliability.

Yamaha's all-new, V6 Offshore series takes the proven 4.2 litre engine platform to the next level by incorporating technological advancements previously only seen on Yamaha's flagship V8 425hp XTO.

The new F225 not only looks good with it's more aggressive styling, but comes with Yamaha's Thrust Enhancing Reverse Exhaust system, which delivers increased prop grip and thrust for improved maneuvering in docking situations and reversing up to your next big catch.

Another cool feature is the new Total TiltTM system which allows the outboard to fully tilt up and down from any position, with a simple double push of the Up or Down Tilt buttons. This not only makes operation easier, but the new mounting bracket system allows the engine to sit higher out of the water when not in use, for improved long-term durability and protection.

When combined with Yamaha's Helm Master EX control system, the new V6 Offshore 225 delivers a boating and fishing experience unlike any else on the water. Technical Specification

HeightX: 640 [25.2] | U: 767 [30.2]

WeightX: 263 | U: 268

Engine24 Valve DOHC with VCT Direct Action 60° - V6

Displacement4169.0

Bore96 x 96

Max RPM5000-6000

LubricationWet-sump

FuelEFI

IgnitionTCI

StarterElectric

Alternator12V-70A with Rectifier Regulator

OperationDigital Electronic Control (DEC)

TiltPower Trim & Tilt with TotalTilt™

GaugesOptional

Network GaugesOptional

Gear Ratio1.75: 1 (Counter Rotating Prop Available)

Engine Details

Horse Power

225